



2 Megapixel, IP outdoor camera with IR Led

- 2 Megapixel IP Camera with Full HD 1080P real time video
- H.264, Mpeg4 compression mode (25 fps max)
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- Built-in Micro SDXC card reader (up to 64GB)

Summary

Aasset Security presents the new 2000 series from Hikvision, a complete line of value IP cameras for Retail and Small Businesses. Based on two possible sensors, in 1.3 to 4 megapixels, they answer to most of installations: indoor, outdoor, day/night with IR projectors, and many image compensation available. The cameras are equipped with varifocal megapixel lens, to help installer to find the right field of view. Finally, they are equipped with SD card slot, for internal storage up to 64GB.

DS-2CD2620F-I

Technical Specifications

Image Sensor	1/2.7" Progressive scan CMOS 2 Megapixel
Pixels - Effective	1920(H) x 1080(V)
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Lens Focal Length	2.8 ~ 12 mm
Horizontal Viewing Angle	113° (Wide) ~ 33.8° (Tele)
Sensitivity Colour	0.01 Lux (50IRE) @ F1.2
Sensitivity B/W	0 Lux LED IR on
Lens Drive Type	Auto Iris (DC)
High Speed Shutter	1/25 ~ 1/100.000 sec
Digital Noise Reduction	3D-DNR, auto
BLC Back Light	On/ Off/ Area/ Level
WDR	D-WDR (Digital wide dynamic range)
Video Compression	H.264, MJPEG, Single/ Dual Stream
Bit Rate	32 Kbps ~ 16 Mbps
Frame Rate	25 fps (1920 x 1080)
Alarm Trigger	Motion detection, Tampering, Network disconnect, IP address conflict, Storage exception
Network Protocol	Bonjour, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, IEEE 802.1 X, IGMP, NTP, PPPoE, QoS, RTCP, RTP, RTSP, SMTP, SNMP, TCP/IP, UDP, UPnP
System Compatibility	CGI, ONVIF, PSIA
Web Browser	Internet Explorer 7.0+, Firefox 3.5+, Chrome 8.0+, Safari 5.0+
Security	Password protection, Watermark
Network Interface	1x 10/100 Base T/TX (RJ-45)
Max. IR Distance	15/30 m (according to scene reflexion)
Protection Rating	IP66
Operating Temperature	-30°C ~ +60°C
Humidity	less than 90%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Power Consumption (W)	7.5
Weight	1.2 kg - 2.65 lbs
Dimensions	∅ 105 x 258.6 mm - 4.13 x 10.18 In

Accessories



DS-1275ZJ
Pole Mount Adapter



DS-1260ZJ
Connecting base for bullet camera