



FEATURES

- RS485 control bus, can control up to 255 pcs speed dome cameras
- All input and output communication port use anti-radar design, powerful anti-jamming performance, the standard transmitting distance is 1200 meters
- Good communication compatibility, built-in Pelco-p, Pelco-d, Hikvision and Dahua protocol
- Keyboard operation password on/off/lock function
- Speed dome camera infinitely variable speed control
- LCD display
- Display the current control address's agreement and baud-rate real time.
- 4 level control speed can be set
- Speed dome ID can be switched directly by pressing 'AUX ON' / 'AUX OFF'.
- Key-press sound volume can be adjusted

SPECIFICATION

Protocol	Pelco-d, Pelco-d, Hikvision, Dahua
Baud rate(bps)	1200, 2400, 4800, 9600, 19200, 38400
Control Address	Control 255 dome camera, decoder at the most, address code:0-255
Communication Mode	RS485 half-duplex
Joystick	control: up, down, left, right
Menu and Key-press	English
Warning Tone	Key-touch beep on/off
Power Supply	DC 12V±10%
Power Consumption	5W MAX
Working Temperature	0°C-50°C
Store Temperature	-20-70°C
Package size(mm)	200x190x110
Weight(Kg)	0.9

DIMENTION

