



SPECIFICATION

| Camera | |
|------------------------|---|
| Sensor | 1/2.8", 2.0 megapixel, progressive scan, CMOS |
| Lens | 3.6mm@F1.8 Angle of view(H): 80.5° |
| Shutter | Auto/Manual, 1/6~1/8000 s |
| Min. Illumination | Colour: 0.06 Lux (F1.4, 50IRE) 0 Lux with IR on |
| Day/Night | IR-cut filter with auto switch (ICR) |
| IR Range | Up to 30m (98 ft) IR range |
| S/N | >50dB |
| WDR | Digital |
| Noise Reduction | 2D/3D |
| Video | |
| Max. Resolution | 1920×1080 |
| Video Compression | H.264/MJPEG |
| Frame Rate | 1080P (1920*1080): Max. 30 fps; 720P (1280*720): Max. 30 fps; D1 (720*576): Max. 25 fps |
| Video Streaming | Triple |
| 9:16 Corridor Mode | Supported |
| ROI | Supported |
| OSD | Up to 8 OSDs |
| Motion Detection | Up to 2 areas |
| Privacy Mask | Up to 4 areas |
| Network | |
| Protocols | IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,DNS,DDNS,NTP,FTP,UPnP,HTTP |
| Compatible Integration | ONVIF |
| Interface | |
| Network | 1 RJ45 10M/100M Base-TX Ethernet |
| General | |
| Power | 12 V DC, or PoE (IEEE802.3 af) |
| | 2.0 W (6.4 W with IR on) |
| Dimensions (L × W × H) | 157.3 × 62.4 × 63 mm (6.2" × 2.5" × 2.5") |
| Weight | 0.45 kg (0.99 lb) |
| Working Environment | -35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 90% RH(non-condensing) |
| Ingress Protection | IP66 |

FEATURES

- Day/night functionality
- Smart IR , up to 30 m (98 ft) IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- 3D DNR (Digital Noise Reduction)
- H.264/MJPEG
- Triple streams
- 9:16 corridor format
- ONVIF Conformance
- Wide temperature range: -35°C to 60°C (-31°F to 140°F)
- Wide voltage range of ±25%
- IP66

DIMENTION

