

# WAR003 AHD 16 Channel 1 SATA



## FEATURES

- Support AHD-M series front-end real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android) .
- Support multiple web browsers (IE, Chrome, Firefox, Safari) ;
- Support more than 20 languages (English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, Chinese, Traditional Chinese, Turkish, etc.) , no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development

## SPECIFICATION

System	
Main processor	Huawei Hi 3531
Video	
video compression	H.264(High Profile)
Encode	16*720P real-time
Decode	1*720P real-time
Multi mode input	Pure Analog: 16*AHD-M; 8*AHD-M; Mixed 4*AHD-M (Analog) +4*720P (Network) ; 8*AHD-M (Analog) +8*720P (Network) Pure Network: 1*1080P+8*720P; 4*1080P; 20* 960H
Audio	
Audio compression	G.711A
Intercom	support
Recording and Playback	
Record mode	Manual>alarm>motion detection>timing
Playback Channels	8 (pure local input mode)
Storage and backup	
Space occupation	960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel
Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	
Video input	16 BNC
Video output	1ch VGA, 1ch HDMI
Audio input	2ch RCA
Audio output	1ch RCA
Alarm input	No
Alarm output	No
Network interface	RJ45 10M/100M Adaptive Ethernet port
PTZ control	One RS485; support multiple PTZ protocols
USB	2 USB ports
Hard disk	1 SATA (Each maximum support 4T)
Other	
Power	12V/2A
Dimension	255mm(length)* 225mm(width)* 60mm(height)

