

WAR008 2SATA 16 Ch Analog HD DVR

SPECIFICATION

System	
Main processor	Huawei Hi 3531+Hi3532
Operating System	Embedded LINUX
Video	
Video compression	H.264
Input	16 channel, BNC
Multi mode input	AHD : AHD1080P 16CH@15fps , AHD720P 16CH@25fps , AHD960H 16CH@25fps
	AHD&IP : AHD1080P 2CH+IP1080P 2CH , AHD1080P 4CH+IP1080P 4CH
	IP : IP1080P 4CH , IP720P 4CH , IP1080 1CH+IP720P 8CH , IP960H 20CH
Audio	
Audio compression	G.711A
Input	4 channel, RCA
Output	1 channel, RCA
Intercom	Support
Display	
Interface	1 HDMI, 1 VGA,
Resolution	1920×1080 , 1440×900 , 1280×1024 , 1280×720 , 1024×768
Display Split	1/4/8/9/16
Privacy Masking	4 rectangular zones (each camera)
Recording	
Video/Audio Compression	H.264/G.711
Resolution	1080P(1920×1080)/720P(1280×720/1280×600)/960H(960×576/960×480)
Record Rate	Main Stream 1080P(1~15fps)/ 720P/960H(1~25fps)
	Extra Stream CIF(1~12fps) / QCIF(1~25fps)
Bit Rate	35~5415Kb/s
Record mode	Manual>alarm>motion detection>timing
Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22× 18), Video Loss & Camera Blank
Alarm input	8 channel
Alarm output	1 channel
Network	
Ethernet	RJ45 (10M/100M)
Network Functions	HTTP , IPv4 , TCP/IP , UPNP , RTSP , NTP , DHCP , DNS , PPOE , DDNS , FTP , IP Filter , Alarm Server , Cloud , PMS , WIFI
Smart Phone	iPhone, iPad, Android, Windows Phone
Playback & Backup	
Sync Playback	8 channel
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup mode	Network backup , USB HDD, USB writer , SATA writer
Storage	
Internal HDD	2 SATA ports, up to 8TB
Auxiliary Interface	
USB Interface	2 USB ports USB2.0
RS485	1 port For PTZ control
General	
Power Supply	12V/4A
Dimension (W× D× H)	350mm * 296mm * 44mm
Temperature	-5°C ~40°C

FEATURES

- Up to 16 Camera with 1080P realtime preview
- Support all channel 1080P@15fps 720P@25fps 960H@25fps
- Support VGA, HDMI 1080P full HD output
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- Support more than 20 languages, no nation boundaries;
- Supporting web, CMS, center platform management software, provide SDK development

DIMENTION

