





FEATURES

- 1/2.7" 2Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920× 1080)
- DWDR, Day/Night(ICR), AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3.6mm fixed lens
- Max. IR LEDs Length 30m
- IP66, PoE, DC12V

DIMENTION



SPECIFICATION

Camera		
Image Sensor		1/2.7" 2Megapixel progressive scan Exmor CMOS
Effective Pixels		1920(H)x1080(V)
Scanning System		Progressive
Electronic Shutter Speed		Auto/Manual, 1s~1/10000s
Min. Illumination		0.025Lux/F2.1(Color), 0Lux/F2.1(IR on)
S/N Ratio		More than 50dB
Video Output		N/A
Camera Features		
Max. IR LEDs Length		30m
Day/Night		Auto(ICR)/Color/B/W
Backlight Compensation		BLC / HLC / DWDR
White Balance		Auto/Manual
Gain Control		Auto/Manual
Noise Reduction		3D
Privacy Masking		Up to 4 areas
Lens		
Focal Length		3.6mm
Max Aperture		F2.1 (F2.0)
Focus Control		Manual
Angle of View		H:93°(63°)
Lens Type		Fixed lens
Mount Type		Board-in Type
Video		
Compression		H.264/H.264H/ H.264B/ MJPEG
Resolution		1080P(1920× 1080)/720P(1280× 720)/D1(704× 576/704× 480)/ CIF(352× 288/352× 240)
Frame	Main Stream	1080P/720P(1 ~ 25/30fps)
Rate	Sub Stream	D1/CIF(1 ~ 25/30fps)
Bit Rate		H.264: 32K ~ 8192Kbps
Corridor Mode		Support
Audio		
Compression		N/A
Interface		N/A
Network		
Ethernet		RJ-45 (10/100Base-T)
Wi-Fi		N/A
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour,
ONVIF		ONVIF , CGI
Max. User Access		20 users
Smart Phone		iPhone, iPad, Android, Windows Phone
Auxiliary Interface		
Memory Slot		N/A
RS485		N/A
Alarm		N/A
PIR Sensor Range		N/A
General		
Power Supply		DC12V , PoE (802.3af)
Power Consumption		5.5W (IR on)
Working Environment		-30°C~+60°C, Less than 95%RH
Ingress Protection		IP67
Vandal Resistance		N/A
Dimensions		Φ70mm× 165mm
Weight		0.38Kg(with package 0.44Kg)

