




FEATURES

- Up to 4 cameras with 1080p realtime preview
- H.264 dual-stream video compression
- Max 200Mbps incoming bandwidth
- Up to 5Mp resolution preview&playback
- HDMI/VGA/BNC simultaneous video output
- 4 channel synchronous realtime playback, GRID interface
- Support Multi-brand network cameras: Arecont Vision, AXIS, Bosch, Brickcom,
- Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.
- ONVIF Version 2.3 conformance
- 3D intelligent positioning with PTZ camera
- Support 2 SATA HDDs up to 8TB, 2 USB(1 USB3.0)
- Support IPC UPnP, 4PoE ports
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DIMENTION



SPECIFICATION

System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Video & Audio	
Input	4 channel
Two-way Talk	1 channel Input, 1 channel Output, BNC
Display	
Interface	1 HDMI, 1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Video/Audio Compression	H.264/MJPEG
Resolution	5Mp(2560×1920)/3Mp(2048×1536)/ 1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	200Mbps
Bit Rate	48~8192Kb/s
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input	4 channel
Alarm Output	2 channel
Playback & Backup	
Sync Playback	1/4
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Network/Internal SATA Device
Network	
Ethernet	1 RJ-45 port (10/100M/1000M)
PoE	4 ports (IEEE802.3af)
Network Functions	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.)
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	2 SATA ports, up to 8TB
Auxiliary Interface	
USB Interface	2 ports (1 Rear USB3.0, 1 Front USB2.0)
RS232	1 port, For PC communication & Keyboard
RS485	1 port For PTZ control
General	
Power Supply	DC12V/4A , PoE DC48V/1.04A
Power Consumption	20W (without HDD) PoE: Max.25.5W for single port
Working Environment	-10°C ~+55°C / 10%~90%RH / 86~106kpa
Dimension(W×D×H)	1U, 375mm×285mm×50mm
Weight	2.0KG(without HDD)

