




## FEATURES

- 1/3" 1.4Megapixel CMOS
- 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switchable
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 3.6mm fixed lens
- Max. IR LEDs length 20m, Smart IR
- IP66, DC12V

## DIMENTION



## SPECIFICATION

|                        |                                                                                                      |
|------------------------|------------------------------------------------------------------------------------------------------|
| Image Sensor           | 1/3" 1.4Megapixel CMOS                                                                               |
| Effective Pixels       | 1305(H)×1049(V)                                                                                      |
| Electronic Shutter     | 1/3s~1/100,000s                                                                                      |
| Video Frame Rate       | 25/50fps@720P                                                                                        |
| Synchronization        | Internal                                                                                             |
| Min. Illumination      | 0.01Lux@F1.2(AGC ON), 0Lux IR on                                                                     |
| Video Output           | 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch) |
| <b>Camera Features</b> |                                                                                                      |
| Max. IR LEDs Length    | 20m, Smart IR                                                                                        |
| Day/Night              | Auto(ICR) / Color / B/W                                                                              |
| Noise Reduction        | 2D/3D                                                                                                |
| OSD Menu               | Support                                                                                              |
| <b>Lens</b>            |                                                                                                      |
| Focal length           | 3.6mm                                                                                                |
| Mount Type             | M12                                                                                                  |
| <b>General</b>         |                                                                                                      |
| Power Supply           | DC12V±10%                                                                                            |
| Power Consumption      | Max 4.2W                                                                                             |
| Working Environment    | -30°C~+60°C / Less than 95%RH (no condensation)                                                      |
| Transmission Distance  | Over 500m via 75-3 coaxial cable                                                                     |
| Ingress Protection     | IP66                                                                                                 |
| Dimensions(W×D×H)      | Φ65mm×154.7mm                                                                                        |
| Weight                 | 0.38kg                                                                                               |
| Others                 | Default: bracket included                                                                            |

