



FEATURES

- 1/3" 2.0 Megapixel CMOS
- 25/30fps@1080P
- High speed, long distance real-time transmission
- HD and standard definition switchable
- Day/Night(ICR), AWB, AGC, BLC, 2D-DNR
- DC12V

SPECIFICATION

Camera	
Image Sensor	1/3" 2.0Megapixel CMOS
Effective Pixels	1920(H)×1080(V)
Electronic Shutter	1/50s~1/100,000s & 1/60s~1/100,000s
Video Frame Rate	25/30fps@1080P
Synchronization	Internal
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Video Output	1-channel BNC HDCVI high definition video output
Camera Features	
Max. IR LEDs Length	N/A
Day/Night	N/A
Noise Reduction	3D
OSD Menu	Support
Lens	
Focal Length	N/A
Angle of View	H:52.2(103.4/79.7/39.0)
Mount Type	CS
General	
Power Supply	DC12V±10%
Power Consumption	Max 3.5W
Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	N/A
Dimensions	Φ94.0mm×79.5mm
Weight	0.33kg

