



## FEATURES

- 1/3" 2Megapixel CMOS
- 25/30fps@1080P
- High speed, long distance real-time transmission
- Day/Night(ICR), AWB, AGC, BLC, 2DNR
- 2.8-12mm motorizes lens
- Max. IR LEDs length 30m
- IP66, DC12V

## SPECIFICATION

|                        |  |
|------------------------|--|
| <b>Camera</b>          |  |
| Image Sensor           | 1/3" 2 Megapixel CMOS                            |
| Effective Pixels       | 1920(H)×1080(V)                                  |
| Electronic Shutter     | 1/50~1/100,000 1/60~1/100,000                    |
| Video Frame Rate       | 25/30fps@1080P                                   |
| Synchronization        | Internal   |
| Min.LLLumination       | 0.01Lux/F1.2, 0 Lux IR on                        |
| Video Output           | 1-channel BNC HDCVI high definition video output |
| <b>Camera Features</b> |  |
| Max. IR LEDs Length    | 30m  |
| Day/Night              | Auto(ICR) / Color / B/W                          |
| Noise Reduction        | 2D   |
| OSD Menu               | Built In   |
| <b>Lens</b>            |  |
| Focal Length           | 2.8-12mm motorizes lens                          |
| <b>General</b>         |  |
| Power Supply           | DC12V  |
| Power Consumption      | Max 3.6W   |
| Working Environment    | -30°C~+60°C / Less than 90%RH (no condensation)  |
| Transmission Distance  | Over 300m via 75-3coaxial cable                  |
| Water Proof Rated      | IP66   |

