




FEATURES

- Day/night functionality
- SmartIR, up to 30 m (98 ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)
- Car-grade LEDs, brighter and uniform light compensation
- Ultra 265,H.265, H.264, MJPEG
- Triple streams
- ROI (Region of Interest)
- ONVIF Conformance
- Wide temperature range: -30°C to 60°C (-22°F to 140°F)
- Wide input voltage range of ±25%
- 2-Axis
- IK10 vandal resistant
- IP66

DIMENTION



SPECIFICATION

Camera	
Sensor	1/2.7", progressive scan, 2.0 megapixel, CMOS
Shutter	Auto/Manual, 1/6~1/100000 s
Min. Illumination	Colour: 0.2 Lux (F2.2, AGC ON) 0 Lux with IR
Lens	2.8 mm@ F2.2
Angle of View (H)	105.2°
Digital noise reduction	2D/3D DNR
IR Range	Up to 30m (98 ft) IR range
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
Defog	Digital Defog
WDR	DWDR
Video	
Max. Resolution	1920×1080
Video Compression	Ultra 265,H.265, H.264,MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	1080P (1920*1080): Max. 25 fps; 720P (1280*720): Max. 25 fps; D1 (720*576): Max. 25 fps
Video Streaming	Triple
HLC	Supported
BLC	Supported
ROI	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
Motion Detection	Up to 4 areas
General Function	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP
Compatible Integration	ONVIF(Profile S, Profile G), API
Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet
General	
Power	12 V DC±25%, PoE (IEEE802.3 af) Power consumption: Max 5.0W
Dimensions (L × W × H)	Φ108.5 x 81 mm (Ø 4.28" x 3.2")
Weight	0.3 kg (0.66 lb)
Working Environment	30°C ~ +60°C (-22°F ~ 140°F), Humidity:10%~95% RH(non-condensing)
Ingress Protection	IP66
Vandal Resistant	IK10

